

# Two Techniques for Fast Computation of Constrained Shortest Paths

Shigang Chen<sup>†</sup>

Meongchul Song<sup>‡</sup>

Sartaj Sahni<sup>†</sup>

<sup>†</sup> Department of Computer & Information Science & Engineering University of Florida

<sup>‡</sup> Systems R&D Laboratories, Samsung Electronics

**Abstract**—Computing constrained shortest paths is fundamental to some important network functions such as QoS routing, MPLS path selection, ATM circuit routing, and traffic engineering. The problem is to find the cheapest path that satisfies certain constraints. In particular, finding the cheapest delay-constrained path is critical for real-time data flows such as voice/video calls. Because it is NP-complete, much research has been designing heuristic algorithms that solve the  $\varepsilon$ -approximation of the problem with an adjustable accuracy. A common approach is to discretize (i.e., scale and round) the link delay or link cost, which transforms the original problem to a simpler one solvable in polynomial time. The efficiency of the algorithms directly relates to the magnitude of the errors introduced during discretization. In this paper, we propose two techniques that reduce the discretization errors, which allows faster algorithms to be designed. Reducing the overhead of computing constrained shortest paths is practically important for the successful design of a high-throughput QoS router, which is limited at both processing power and memory space. Our simulations show that the new algorithms reduce the execution time by an order of magnitude on power-law topologies with 1000 nodes. The reduction in memory space is similar.

## I. INTRODUCTION

A major obstacle against implementing distributed multimedia applications (e.g., web broadcasting, video conferencing, and remote diagnosis) is the difficulty of ensuring QoS (Quality of Service) over the Internet. A fundamental problem that underlies many important network functions such as QoS routing, MPLS path selection, and traffic engineering, is to find the constrained shortest path — the cheapest path that satisfies a set of constraints [1], [2], [3], [4], [5], [6], [7], [8], [9], [10]. For interactive real-time traffic, the delay-constrained least-cost path has particular importance [11]. It is the cheapest path whose end-to-end delay is bounded by the delay requirement of a time-sensitive data flow. The additional bandwidth requirement, if there is one, can be easily handled by a pre-processing step that prunes the links without the required bandwidth from the graph.

The algorithms for computing the constrained shortest paths can be used in many different circumstances, for instance, laying out virtual circuits in ATM networks, establishing wavelength-switching paths in fiber-optics networks, constructing label-switching paths in MPLS based on the QoS requirements in the service contracts, or applying together with RSVP. There are two schemes of implementing the QoS routing algorithms on routers. The first scheme is to implement them as on-line algorithms that process the

routing requests as they arrive. In practice, on-line algorithms are not always desired. When the request arrival rate is high (major gateways may receive thousands or tens of thousands of requests every second), even the time complexity of Dijkstra's algorithm will overwhelm the router if it is executed on a per-request basis.<sup>1</sup> To solve this problem, the second scheme is to extend a link-state protocol (e.g. OSPF) and periodically pre-compute the cheapest delay-constrained paths for all destinations, for instance, for voice traffic with an end-to-end delay requirement of 100 ms. The computed paths are cached for the duration before the next computation. This approach provides support for both constrained unicast and constrained multicast. The computation load on a router is independent of the request arrival rate. Moreover, many algorithms, including those we will propose shortly, have the same time complexity for computing constrained shortest paths *to all destinations* or *to a single destination*. This paper studies the second scheme.

A path that satisfies the delay requirement is called a *feasible path*. Finding the cheapest (least-cost) feasible path is NP-complete. There has been considerable work in designing heuristic solutions for this problem. Xue [12] and Juttner et al. [13] used the Lagrange relaxation method to approximate the delay-constrained least-cost routing problem. However, there is no theoretical bound on how large the cost of the found path can be. Korkmaz and Krunk used a non-linear target function to approximate the multi-constrained least-cost path problem [14]. It was proved that the path that minimizes the target function satisfies one constraint and the other constraints multiplied by  $\sqrt[k]{\lambda}$ , where  $\lambda$  is a predefined constant and  $k$  is the number of constraints. However, no known algorithm can find such a path in polynomial time. [14] proposed a heuristic algorithm, which has the same time complexity as Dijkstra's algorithm. It does not provide a theoretical bound on the property of the returned path, nor provide conditional guarantee in finding a feasible path when one exists. In addition, because the construction of the algorithm ties to a particular destination, it is not suitable for computing constrained paths from one source to all destinations. For this task, it is slower than the algorithms proposed in this paper by two orders of magnitude based on our simulations.

Another thread of research in this area is to design polynomial time algorithms that solves the NP-complete problem with an accuracy that is theoretically bounded. Let

<sup>1</sup>Note that path caching does not eliminate the problem of finding constrained shortest paths because those paths must be calculated before being cached.

$m$  and  $n$  be the number of links and the number of nodes in the network, respectively. Given a small constant  $\varepsilon$ , Hassin's algorithm [15] has a time complexity of  $O(\frac{mn}{\varepsilon} \log \log \frac{UB}{LB})$ , where UB and LB are the costs of the fastest path and the cheapest path from the source node to the destination node, respectively. The algorithm finds a feasible path if there exists one. The cost of the path is within the cost of the cheapest feasible path multiplied by  $(1 + \varepsilon)$ . Lorenz and Raz improved the time complexity to  $O(mn(1/\varepsilon + \log n))$  [16]. Chen and Nahstedt solved a similar problem in time  $O((m + n \log n)x)$ , where  $x = O(n/\varepsilon)$  in order to achieve the  $\varepsilon$ -approximation [17]. Goel et al.'s algorithm [18] has the best-known complexity of  $O((m + n \log n)\frac{L}{\varepsilon})$ , where  $L$  is the length (hops) of the longest path in the network. However, its approximation model is different. It computes a path whose cost is no more than the cost of the cheapest feasible path, while the delay of the path is within  $(1 + \varepsilon)$  of the delay requirement. The algorithms proposed in this paper follow Goel's model.

One common technique of the above algorithms [15], [17], [18] is to discretize the link delay (or link cost). Due to the discretization, the possible number of different delay values (or cost values) for a path is reduced, which makes the problem solvable in polynomial time. The effectiveness of this technique depends on how much error is introduced during the discretization. The existing discretization approaches have either positive discretization error for every link or negative error for every link. Therefore, the discretization error on a path is statistically proportional to the path length as the errors on the links along the path add up. In order to bound the maximum error, the discretization has to be done at a fine level, which leads to high execution time of the algorithms.

Given the limited resources and ever-increasing tasks of the routers, it is practically important to improve the efficiency of the network functions. While QoS routing is expensive due to its non-linear nature, it has particular significance to reduce the router's overhead in computing the constrained shortest paths. In this paper, we propose two techniques, *randomized discretization* and *path delay discretization*, which reduce the discretization errors and allow faster algorithms to be designed. The randomized discretization cancels out the link errors along a path. The larger the topology, the greater the error reduction. The path delay discretization works on the path delays instead of the individual link delays, which eliminates the problem of error accumulation. Based on these techniques, we design fast algorithms to solve the  $\varepsilon$ -approximation of the constrained shortest-path problem. We prove the correctness and complexities of the algorithms. Although the new algorithms have the same worst-case complexity as Goel et al.'s algorithm [18], we believe (and our simulations suggest) that they run much faster on the average case. The simulations show that the new algorithms are faster than Goel et al.'s algorithm by an order of magnitude on power-law topologies with 1000 nodes.

The rest of the paper is organized as follows. Section II reviews the existing approaches. Section III describes the randomized discretization, and Section IV describes the path delay discretization. Section V and VI provide analytical

and simulation results, respectively. Section VII draws the conclusion.

## II. PROBLEM DEFINITION AND EXISTING DISCRETIZATION APPROACHES

Consider a network  $G\langle V, E \rangle$ , where  $V$  is a set of  $n$  nodes and  $E$  is a set of  $m$  directed links connecting the nodes. The delay and the cost of a link  $(u, v) \in E$  are denoted as  $d(u, v)$  and  $c(u, v)$ , respectively. The delay and the cost of a path  $P$  are denoted as  $d(P)$  and  $c(P)$ , respectively.  $d(P) = \sum_{(u,v) \in P} d(u, v)$ , and  $c(P) = \sum_{(u,v) \in P} c(u, v)$ . Let  $l(P)$  be the length (number of hops) of  $P$ , and  $L$  be the length of the longest path in the network.

Given a delay requirement  $r$ ,  $P$  is called a *feasible path* if  $d(P) \leq r$ . Given a source node  $s$ , let  $V_s$  be the set of nodes to which there exist feasible paths from  $s$ . For any  $t \in V_s$ , the *cheapest feasible path*  $P_{s,t}$  from  $s$  to  $t$  is defined as

$$\begin{aligned} d(P_{s,t}) &\leq r \\ c(P_{s,t}) &= \min\{c(P) \mid d(P) \leq r, \forall \text{path } P \text{ from } s \text{ to } t\} \end{aligned}$$

The *delay-constrained least-cost routing* problem (DCLC) is to find the cheapest feasible paths from  $s$  to all nodes in  $V_s$ , which is NP-complete [19]. However, if the link delays are all integers and the delay requirement is bounded by an integer  $\lambda$ , the problem can be solved in time  $O((m + n \log n)\lambda)$  by Joksch's dynamic programming algorithm [20] or the extended Dijkstra's algorithm [17].

Joksch's algorithm is described as follows.  $\forall v \in V, i \in [0.. \lambda]$ , let  $w[v, i]$  be a variable storing the cost of the cheapest path  $P$  from  $s$  to  $v$  with  $d(P) \leq i$ , and  $\pi[v, i]$  storing the last link of the path. Initially,  $w[v, i] = \infty, \forall v \neq s$ , and  $w[s, i] = 0$ .  $\pi[v, i] = \text{NIL}$ . Assuming that all link delays are positive, the dynamic programming is given below.

$$\begin{aligned} w[v, i] &= \min\{w[v, i - 1], w[u, i - d(u, v)] + c(u, v), \\ &\quad \forall (u, v) \in E, d(u, v) \leq i\} \end{aligned}$$

Now suppose the link delays are allowed to be zero. We need to add one more step. Let  $G_z$  be the subgraph consisting of all zero-delay links. For each  $i \in [0.. \lambda]$ , immediately after Joksch's algorithm calculates  $w[v, i], \forall v \in V$ , Dijkstra's algorithm is executed on  $G_z$  to improve  $w[v, i]$  on zero-delay paths [18].

The above polynomially-solvable special case with integer delays points out a heuristic solution for the general NP-complete problem with arbitrary delays. The idea is to discretize (scale and then round) arbitrary link delays to integers [15], [17], [21], [18]. There are two existing discretization approaches, *round to ceiling* [17] and *round to floor* [18]. Both approaches map the delay requirement  $r$  to a selected integer  $\lambda$ , and then discretize the link delays as follows.

**Round to ceiling (RTC):** For every link  $(u, v)$ , the delay value is divided by  $\frac{r}{\lambda}$ . If the result is not an integer, it is rounded to the nearest larger integer.

$$d^c(u, v) = \lceil \frac{d(u, v)}{r} \lambda \rceil \quad (1)$$

**Round to floor (RTF):** For every link  $(u, v)$ , the delay value is divided by  $\frac{r}{\lambda}$ . If the result is not an integer, it is rounded to the nearest smaller integer.

$$d^f(u, v) = \lfloor \frac{d(u, v)}{r} \lambda \rfloor \quad (2)$$

The value of  $\lambda$  controls the rounding error (up to  $\frac{r}{\lambda}$ ) introduced by discretization. With a larger  $\lambda$ , the rounding error accounts for a smaller portion of the link delay. When  $\lambda$  is large enough and thus the discretization error is small enough, we can approximate the DCLC problem by a new problem with integer delays after discretization. The solution to the new problem will serve as the solution of the original problem. However the computation overhead is directly related to  $\lambda$ .

After discretizing the link delays by RTC or RTF, either Joksch's algorithm or the extended Dijkstra's algorithm can solve the  $\varepsilon$ -approximation of DCLC, which is to find a path  $P$  for every node  $t \in V_s$ , such that

$$\begin{aligned} d(P) &\leq (1 + \varepsilon)r \\ c(P) &\leq c(P_{s,t}) \end{aligned}$$

where  $\varepsilon$  is a small percentage. The delay of the path is allowed to exceed the requirement by a percentage of no more than  $\varepsilon$ , while the cost should be no more than that of the cheapest feasible path  $P_{s,t}$ . Using RTF, the delay scaling algorithm (DSA) proposed by Goel et al. achieves the best time complexity  $O((m+n \log n)L/\varepsilon)$  among all existing algorithms [18].

The discretization error of a link  $(u, v)$  is defined as

$$\Delta^c(u, v) = d(u, v) - d^c(u, v) \frac{r}{\lambda} \quad (3)$$

$$\Delta^f(u, v) = d(u, v) - d^f(u, v) \frac{r}{\lambda} \quad (4)$$

The discretization error of a path  $P$  is defined as

$$\Delta^c(P) = \sum_{(u,v) \text{ on } P} \Delta^c(u, v) \quad (5)$$

$$\Delta^f(P) = \sum_{(u,v) \text{ on } P} \Delta^f(u, v) \quad (6)$$

By (1), we know that  $\Delta^c(u, v) \leq 0$  is true for all links  $(u, v)$ . Therefore,  $\Delta^c(P) \leq 0$  is true for all paths  $P$ . Similarly, by (4),  $\Delta^f(u, v) \geq 0$  and  $\Delta^f(P) \geq 0$  are always true.

### III. RANDOMIZED DISCRETIZATION

RTC creates negative rounding errors on links. The error accumulates along a path. The accumulated error is proportional to the path length. The larger the topology, the longer a path, the larger the accumulated error. The same thing is true for RTF, which has positive rounding errors on links. In order to achieve  $\varepsilon$ -approximation, the accumulated error on a path cannot be too large. To reduce the error on a path, the existing algorithms based on RTC or RTF must reduce the discretization errors on the links by using a large  $\lambda$  value. Given the time complexity  $O((m+n \log n)\lambda)$ , the computation time is increased in proportion to  $\lambda$ .

The insight is that if we can reduce the error introduced by discretization without using a larger  $\lambda$ , we can improve the

performance of the algorithm. We develop two new techniques. The first one is called randomized discretization. It rounds to ceiling or to floor according to certain probabilities. The idea is for some links to have positive errors and some links to have negative errors. Positive errors and negative errors cancel out one another along a path in such a way that the accumulated error is minimized statistically. We will prove that, when the following discretization approach is used, the mean of the accumulated error on a path  $P$  is zero and the standard deviation is bounded by  $\frac{r\sqrt{l(P)}}{2\lambda}$ . In comparison, the mean of the accumulated error is  $-\frac{r}{2\lambda}l(P)$  for RTC and  $\frac{r}{2\lambda}l(P)$  for RTF.

**Round randomly (RR):** For every link  $(u, v)$ , the delay value is divided by  $\frac{r}{\lambda}$ . If the result is not an integer, it is rounded to the nearest smaller integer or to the nearest larger integer randomly such that the mean error is zero.

$$d^r(u, v) = \begin{cases} \lceil \frac{d(u, v)}{r} \lambda \rceil & \text{with prob. } p_1 = \frac{d(u, v)}{r} \lambda - \lfloor \frac{d(u, v)}{r} \lambda \rfloor \\ \lfloor \frac{d(u, v)}{r} \lambda \rfloor & \text{with prob. } p_2 = 1 - p_1 \end{cases} \quad (7)$$

The discretized delay of a path  $P$  is

$$d^r(P) = \sum_{(u,v) \in P} d^r(u, v) \quad (8)$$

The discretization error of a link  $(u, v)$  is

$$\Delta^r(u, v) = d(u, v) - d^r(u, v) \frac{r}{\lambda} \quad (9)$$

and the discretization error of a path  $P$  is

$$\Delta^r(P) = \sum_{(u,v) \text{ on } P} \Delta^r(u, v) = d(P) - d^r(P) \frac{r}{\lambda} \quad (10)$$

We design the randomized discretization algorithm (RDA), which is based on Dijkstra's algorithm but considers two additive metrics, *delay* and *cost*. It uses RR to discretize the link delays. We will prove that it solves the  $\varepsilon$ -approximation of DCLC.

The pseudo code of RDA is given below. A two-dimensional array,  $w[v, i]$ ,  $\forall v \in V, i \in [0.. \lambda]$ , stores the cost of the cheapest path  $P$  from  $s$  to  $v$  with  $d^r(P) = i$ . Another two dimensional array,  $\pi[v, i]$ , stores the last link of the path. An auxiliary two-dimensional array,  $\delta[v, i]$ , keeps track of the minimum discretization error on paths whose discretized delays are  $i$  from node  $s$  to node  $v$ .

Given any value of  $\lambda$ ,  $\text{RDA\_Dijkstra}(G, s, \lambda)$  computes  $w[v, i]$  and  $\pi[v, i]$ . For any destination  $v$ , the function finds the cheapest paths at different path delays,  $d^r(P) \in [0.. \lambda]$ . Let  $P^v$  be the cheapest among these paths.  $\text{RDA}(G, s)$  iteratively calls  $\text{RDA\_Dijkstra}$  with an increasing  $\lambda$  until the delay of  $P^v$  is smaller than  $(1 + \varepsilon)r$  for all  $v$ .

RDA assumes a preprocessing step that removes all nodes to which there are no feasible paths from  $s$ . This step can be done by calling Dijkstra's algorithm because only one metric (*delay*) is considered.

Initialize( $V, s, \lambda$ )

1. **for** each vertex  $v \in V$ , each  $i \in [0.. \lambda]$  **do**
2.      $w[v, i] := \infty$ ,  $\pi[v, i] := \text{NIL}$ ,  $\delta[v, i] := \infty$
3.      $w[s, 0] := 0$ ,  $\delta[s, i] := 0$

```

Relax_RDA( $u, v, i, \lambda$ )
4.    $i' := i + d^r(u, v)$ 
5.    $error := \delta[u, i] + \Delta^r(u, v)$ 
6.   if  $error < 0$  then
7.      $error := error + r/\lambda$ 
8.      $i' := i' - 1$ 
9.   if  $i' \leq \lambda$  and  $w[v, i'] > w[u, i] + c(u, v)$  then
10.     $w[v, i'] := w[u, i] + c(u, v)$ 
11.     $\pi[v, i'] := u$ 
12.     $\delta[v, i'] := \min\{\delta[v, i'], error\}$ 

```

```

RDA_Dijkstra( $G, s, \lambda$ )
13.  Initialize( $V, s, \lambda$ )
14.  for  $i = 0$  to  $\lambda$  do
15.     $Q := V$ 
16.    while  $Q \neq \emptyset$  do
17.       $u := \text{Extract\_Min}(Q)$ 
18.      if  $w[u, i] = \infty$  then
19.        break out of the while loop
20.      for every adjacent node  $v$  of  $u$  do
21.        Relax_RDA( $u, v, i, \lambda$ )

```

```

RDA( $G, s$ )
22.   $\lambda := \lambda_0$ 
23.  do
24.     $\lambda := 2\lambda$ 
25.    RDA_Dijkstra( $G, s, \lambda$ )
26.  while  $\exists v \in V, d(P^v) > (1 + \varepsilon)r,$ 
    where  $P^v$  is the path with  $\min\{w[v, i] \mid i \in [0..\lambda]\}$ 

```

The correctness of the algorithm is given in the theorem below. The proof can be found in Appendix A.

*Theorem 1:* RDA solves the  $\varepsilon$ -approximation of DCLC in time  $O((m + n \log n)L/\varepsilon)$ .

RDA has the same worst-case time complexity as DSA [18], which uses RTF. The reason is that, *in the worst case*, it could happen that  $d^r(u, v) = d^f(u, v)$  for all links  $(u, v)$ , which makes RR identical to RTF. But such occurrence is *extremely unlikely*. More important than the worst-case complexity is the average-case running time of the algorithm. By its nature, RR is a statistical approach. It does not improve the performance of the algorithm for the rare worst case when round-to-floor happens at all links, but it improves for an average case where round-to-floor and round-to-ceiling happen probabilistically as specified in (7). Because positive errors and negative errors cancel out each other along a path, RDA requires a much smaller  $\lambda$  to complete than DSA, which accumulates positive errors on a path. Consequently, RDA runs much faster than DSA on average, which will be evident from our analytical and simulation results.

#### IV. PATH DELAY DISCRETIZATION

Each unit of discretized delay represents the amount  $\frac{r}{\lambda}$  of real delay. Due to rounding, each time discretization is performed, a discretization error up to  $\frac{r}{\lambda}$  is introduced between the discretized delay and the real delay. The maximum discretization error of a path is determined by the number of times that discretization is performed on the path. RTF, RTC, and RR perform discretization at the link level. Because

discretization is carried out on each link, the maximum error on the path is linear to the path length. In order to achieve  $\varepsilon$ -approximation, the accumulated error on a path cannot be too large. There are two ways to reduce the error. One is to use a larger  $\lambda$ , which increases the execution time of an algorithm whose complexity is linear to  $\lambda$ . The other way is to reduce the number of discretizations performed on the path.

Our second technique to control error is to perform discretization on the path level, using the interval partitioning method for combinatorial approximation [22]. For a path  $P$ , ideally, discretization is performed once as follows.

$$d'(P) = \lfloor \frac{d(P)}{r} \lambda \rfloor \quad (11)$$

Because only one discretization is performed, the maximum discretization error on any path is bounded by  $\frac{r}{\lambda}$ , independent of the path length.

Below we design the path discretization algorithm (PDA) based on the above intuition. The algorithm solves the  $\varepsilon$ -approximation with the same worst-case complexity as RDA. However, its average execution time is better than RDA according to our simulations. An auxiliary two-dimensional array,  $z[v, i]$ , keeps track of the minimum delay of paths whose discretized delays are  $i$  from node  $s$  to node  $v$ .

PDA\_Dijkstra is omitted because it is identical to RDA\_Dijkstra except that it calls Relax\_PDA.

```

Initialize( $V, s, \lambda$ )

```

```

1.  for each vertex  $v \in V$ , each  $i \in [0..\lambda]$  do
2.     $w[v, i] := \infty, \pi[v, i] := \text{NIL}, z[v, i] := \infty$ 
3.     $w[s, 0] := 0, z[s, 0] := 0$ 

```

```

Relax_PDA( $u, v, i, \lambda$ )

```

```

4.   $i' := \lfloor \frac{z[u, i] + d(u, v)}{r} \lambda \rfloor$ 
5.  if  $i' \leq \lambda$  and  $w[v, i'] > w[u, i] + c(u, v)$  then
6.     $w[v, i'] := w[u, i] + c(u, v)$ 
7.     $\pi[v, i'] := u$ 
8.     $z[v, i'] := \min\{z[v, i'], z[u, i] + d(u, v)\}$ 

```

```

PDA( $G, s$ )

```

```

9.   $\lambda := \lambda_0$ 
10. do
11.   $\lambda := 2\lambda$ 
12.  PDA_Dijkstra( $G, s, \lambda$ )
13.  while  $\exists v \in V, d(P^v) > (1 + \varepsilon)r,$ 
    where  $P^v$  is the path with  $\min\{w[v, i] \mid i \in [0..\lambda]\}$ 

```

The correctness of the algorithm is given in the theorem below. The proof can be found in Appendix B.

*Theorem 2:* PDA solves the  $\varepsilon$ -approximation of DCLC in time  $O((m + n \log n)L/\varepsilon)$ .

#### V. ANALYSIS

When RTF is used, all links have non-negative discretization errors with a tight upper bound of  $\frac{r}{\lambda}$ . Hence, the discretization errors on links of a path  $P$  will add up to a non-negative value with a tight upper bound of  $\frac{r}{\lambda}l(P)$ , which is linear to the path length. Statistically, the longer the path, the larger the error. For

instance, if  $\Delta^f(u, v), \forall(u, v) \in P$ , is uniformly distributed in  $[0, \frac{r}{\lambda})$ , the mean of  $\Delta^f(P)$  is  $\frac{r}{2\lambda}l(P)$ .

When RTC is used, all links have non-positive discretization errors with a tight lower bound of  $-\frac{r}{\lambda}$ . If  $\Delta^c(u, v), \forall(u, v) \in P$ , is uniformly distributed in  $(-\frac{r}{\lambda}, 0]$ , the mean of  $\Delta^c(P)$  is  $-\frac{r}{2\lambda}l(P)$ .

The error of the proposed path-delay discretization is always non-negative with a tight upper bound of  $\frac{r}{\lambda}$ , independent of the path length.

To study RR, we model  $d(u, v), \forall(u, v) \in E$ , as a random variable. For any path  $P$ ,  $\Delta^r(P)$  is also a random variable. Assuming the delays of different links are independent, we prove the following theorem in Appendix C.

*Theorem 3:* Given a path  $P$ , the mean of  $\Delta^r(P)$  is zero and the standard deviation of  $\Delta^r(P)$  is at most  $\frac{r\sqrt{l(P)}}{2\lambda}$ , regardless of the probability distributions of the link delays.

We also perform simulations to compare the discretization errors of different approaches. Fig. 1 shows how the discretization errors of RTF, RTC and RR grow with the path length. The link delay is randomly generated, following an exponential distribution with a mean at 100 ms. The discretization errors of RTF and RTC grow linearly with the path length,<sup>2</sup> while the error of RR grows sublinearly. Fig. 2 shows that, in order to achieve certain discretization error goal, RR requires much smaller  $\lambda$  than RTF and RTC, which means that algorithms based on RR are likely to have less execution time.

## VI. SIMULATION

### A. Simulation Setup

The simulation uses two types of network topologies that are generated based on the Power-Law model [23] and the Waxman model [24]. In a Power-Law topology, the degrees of 10% nodes are one, and the degrees of other nodes follow a power law distribution, i.e., the frequency  $f_d$  of a degree is proportional to the degree  $d$  ( $\geq 2$ ) raised to the power of a constant  $O = -2.2$ .

$$f_d \propto d^O$$

After each node is assigned a degree according to the power law distribution, a spanning tree is formed among the nodes to ensure a connected graph. Additional links are inserted to fulfill the remaining degrees of every node with the neighbors selected according to probabilities proportional to their respective unfulfilled degrees. A Waxman topology is formed as follows: the nodes are randomly placed in a one-by-one square, and the probability of creating a link between node  $u$  and node  $v$  is

$$p(u, v) \propto e^{-d(u, v)/\beta L}$$

<sup>2</sup>When the link delay follows an exponential distribution, the average error caused by RTF is smaller than that caused by RTC. However, when the link delay follows a uniform distribution, the average error by RTF is the same as that by RTC.

where  $d(u, v)$  is the distance between  $u$  and  $v$ ,  $\beta = 0.6$ , and  $L$  is the maximum distance between any two nodes. The average node degree is 3.

The default simulation parameters are: The link delays (costs) are randomly generated, following the exponential distribution with a mean of 100.  $\varepsilon = 0.1$ .  $\lambda_0 = 3$ . Each data point is the average over 1000 randomly generated routing requests. More specifically, we randomly generate ten topologies. On each topology, 100 routing requests are generated with the source node randomly selected from the topology. We run DSA, RDA, and PDA to find a cheapest feasible path to every destination for which a feasible path exists. All simulations were done on a PC with PIV 2GHz CPU and 512 Megabytes memory.

The performance metrics used to evaluate the routing algorithms are defined as follows.

$$\begin{aligned} \text{avg execution time} &= \frac{\text{total execution time for all requests}}{\text{total number of routing requests}} \\ \text{avg cost} &= \frac{\text{total cost of returned paths}}{\text{number of returned paths}} \\ \text{success rate} &= \frac{\text{number of returned paths that are feasible}}{\text{number of returned paths}} \end{aligned}$$

All algorithms under simulation guarantee that the delay of any returned path is bounded by  $(1 + \varepsilon)r$ .

### B. Comparing RDA and PDA with DSA

We compare RDA and PDA with DSA [18], which is the best known  $\varepsilon$ -approximation algorithm for DCLC. Fig. 3 shows the simulation results on Power-Law topologies with 500 nodes. Both RDA and PDA are much faster than DSA, with PDA achieving the best execution time. The average costs of the three algorithms are comparable. The success ratio of RDA is slightly better than the other two. Because the three algorithms are close in terms of average cost and success rate in all simulations, we shall focus on execution time in the sequel.

Fig. 4 compares DSA, RDA, and PDA on Waxman topologies with 1000 nodes. Both RDA and PDA again outperform DSA significantly.

Fig. 5 compares the scalability of the three algorithms with respect to the network size. The performance gap between RDA/PDA and DSA increases for larger topologies. The improvement exceeds an order of magnitude for 1000-node networks.

Fig. 6 compares the algorithms with different  $\varepsilon$  values. The performance gap between RDA/PDA and DSA increases when  $\varepsilon$  is smaller, i.e., the  $\varepsilon$ -approximation is performed at the finer level.

In summary, the simulation results confirmed our basic idea that the execution time could be greatly improved by reducing the discretization error, which was achieved very effectively by RDA and PDA. With 1000 nodes and one constraint, RDA and PDA computes the constrained shortest paths within 38 milliseconds and 25 milliseconds, respectively, which makes them practical solutions for routers to compute the QoS routing paths periodically.




Fig. 1. Compare the average discretization errors of RTF, RTC and RR with respect to different path lengths. The vertical axis is the average of  $|\Delta^f(P)|$ ,  $|\Delta^c(P)|$ , or  $|\Delta^r(P)|$  over 10000 sample paths.




Fig. 2. Compare the average discretization errors of RTF, RTC and RR with respect to different  $\lambda$  values. The vertical axis is the average of  $|\Delta^f(P)|$ ,  $|\Delta^c(P)|$ , or  $|\Delta^r(P)|$  over 10000 sample paths.

TABLE I

EXECUTION TIME (MILLISECONDS) OF FINDING DELAY-CONSTRAINED LEAST-COST PATHS FROM A SOURCE TO ALL DESTINATIONSON ON POWER-LAW TOPOLOGIES

no. of nodes	RDA	PDA	H_MCOP
100	1.3	0.8	35.2
200	3.1	2.2	159.4
300	5.8	3.8	369.5
400	8.3	6.9	673.4
500	13.3	9.4	1092.2
600	19.6	12.6	1615.6
700	25.3	17.0	2285.9
800	32.1	20.8	3024.2
900	40.4	26.5	3946.1
1000	48.2	32.0	4964.8

### C. Comparing RDA and PDA with H\_MCOP

We compare RDA and PDA with a fast heuristic algorithm H\_MCOP [14], whose time complexity is the same as that of Dijkstra's algorithm. H\_MCOP does not solve the  $\varepsilon$ -approximation of DCLC. Its goal is to use heuristics to greatly reduce the computation time. To construct a feasible path with low cost from a particular source node to a particular destination

node, H\_MCOP requires building a shortest-path tree from all nodes to the destination node and a tree from the source node to all nodes. By the algorithm's two-tree design, it is efficient in computing a low-cost feasible path from one source to one destination, but it is not suitable to find low-cost paths from one source to all destinations. To solve this problem, H\_MCOP would have to repeat  $n$  times, one for each destination and with a total time complexity of  $O(nm + n^2 \log n)$ . In comparison, RDA and PDA solve the  $\varepsilon$ -approximation of DCLC, and they find constrained shortest paths for all destinations with the same complexity  $O((m+n \log n) \frac{L}{\varepsilon})$  as finding a constrained shortest path for a single destination.

The comparison of RDA/PDA and H\_MCOP is made under two scenarios. The first scenario is to use them as on-line algorithms that process delay-constrained least-cost unicast routing requests as they arrive. The results are shown in Fig. 7. H\_MCOP has also a parameter called  $\lambda$  for a different purpose, which is however insignificant when there is only one constraint (for delay). H\_MCOP significantly outperforms RDA/PDA in average execution time, RDA/PDA are better in terms of average cost and success rate because they relax the delay requirement by a factor of  $(1 + \varepsilon)$ . H\_MCOP is a more efficient *on-line algorithm* than RDA/PDA.




Fig. 3. Compare DSA, RDA, and PDA on Power-Law topologies. Both RDA and PDA run much faster than DSA. They run slower than Dijkstra's algorithm, but achieve much smaller average path cost. The success rates of DSA, RDA, and PDA are comparable, with RDA slightly better.

In practice, on-line algorithms are not always desired. When the request arrival rate is high (major gateways may receive thousands or tens of thousands of requests every second), even the time complexity of Dijkstra's algorithm (executed on a per-request basis) will overwhelm the router. One typical approach to solve this problem is to extend a link-state protocol (e.g. OSPF) and periodically pre-compute delay-constrained least-cost paths for all destinations. In this way, the computation load on a router is independent of the request arrival rate. Under such scenario, RDA/PDA significantly outperforms H\_MCOP by orders of magnitude when the number of nodes is large, as shown in Table I.

Therefore, H\_MCOP is more suitable as an on-line algorithm,




Fig. 4. Compare DSA, RDA, and PDA on Waxman topologies. Both RDA and PDA run much faster than DSA. PDA is slightly better than RDA.




Fig. 5. Scalability comparison. The delay requirement is 1500. Both RDA and PDA scale much better than DSA, with PDA the best.

while RDA/PDA are more suitable to calculate DCLC paths from one source to all destinations so that a routing table for certain QoS service class can be established. In addition, RDA/PDA are the choice when a constrained multicast tree is calculated centrally.

## VII. CONCLUSION

In this paper, we proposed two techniques, randomized discretization and path delay discretization, to design fast algorithms for computing constrained shortest paths. While the previous approaches (RTF and RTC) build the discretization




Fig. 6. Compare DSA, RDA, and PDA with respect to different  $\epsilon$  values. The delay requirement is 1500, and the network size is 500. Both RDA and PDA run much faster than DSA. PDA is slightly better than RDA.

error along a path, the new techniques either make the link errors to cancel out each other along the path or treat the path delay as a whole for discretization, which results in much smaller errors. The algorithms based on these techniques run much faster than the best existing algorithm that solves the  $\epsilon$ -approximation of DCLC.

## REFERENCES

- [1] S. Chen and K. Nahrstedt, "An Overview of Quality-of-Service Routing for the Next Generation High-Speed Networks: Problems and Solutions," *IEEE Network, Special Issue on Transmission and Distribution of Digital Video*, December 1998.
- [2] R. Guerin and A. Orda, "QoS-based Routing in Networks with Inaccurate Information: Theory and Algorithms," *IEEE INFOCOM'97, Japan*, April 1997.
- [3] T. Korkmaz and M. Krunz, "Source-oriented topology aggregation with multiple QoS parameters in hierarchical ATM networks," *IEEE IWQoS'99*, June 1999.
- [4] Danny Raz and Yuval Shavitt, "Optimal Partition of QoS Requirements with Discrete Cost Functions," *IEEE INFOCOM'2000*, March 2000.
- [5] J. L. Sobrinho, "Algebra and Algorithms for QoS Path Computation and Hop-by-Hop Routing in the Internet," *IEEE INFOCOM'2001*, April 2001.
- [6] Z. Wang and Jon Crowcroft, "QoS Routing for Supporting Resource Reservation," *IEEE JSAC*, September 1996.
- [7] X. Yuan, "Heuristic Algorithms for Multi-Constrained Quality of Service Routing," *IEEE INFOCOM'2001*, April 2001.
- [8] A. Orda and A. Sprintson, "Efficient Algorithms for Computing Disjoint QoS Paths," *IEEE INFOCOM'2004*, March 2004.
- [9] Y. Xiao, K. Thulasiraman, and G. Xue, "Approximation and Heuristic Algorithms for Delay Constrained Path Selection under Inaccurate State Information," *The first International Conference on Quality of Service in Heterogeneous Wired/Wireless Networks (QShine)*, October 2004.
- [10] Y. Xiao, K. Thulasiraman, and G. Xue, "Constrained Shortest Link-Disjoint Paths Selection: A Network Programming Based Approach," *to appear in IEEE Transactions on Circuits and Systems*.
- [11] H. F. Salama, D. S. Reeves, and Y. Viniotis, "A Distributed Algorithm for Delay-Constrained Unicast Routing," *IEEE INFOCOM'1997*, pp. 84–91, April 1997.
- [12] G. Xue, "Primal-Dual Algorithms for Computing Weight-Constrained Shortest Paths and Weight-Constrained Minimum Spanning Trees," *IEEE IPCCC'2000*, February 2000.
- [13] A. Juttner, B. Szviatovszki, I. Mecs, and Z. Rajko, "Lagrange Relaxation Based Method for the QoS Routing Problem," *IEEE INFOCOM'2001*, April 2001.
- [14] T. Korkmaz and M. Krunz, "Multi-Constrained Optimal Path Selection," *IEEE INFOCOM'2001*, April 2001.
- [15] R. Hassin, "Approximation Schemes for the Restricted Shortest Path Problem," *Mathematics of Operations Research*, vol. 17, pp. 36–42, 1992.
- [16] D. Lorenz and D. Raz, "A Simple Efficient Approximation Scheme for the Restricted Shortest Path Problem," *Bell Labs Technical Memorandum*, 1999.
- [17] S. Chen and K. Nahrstedt, "On Finding Multi-Constrained Paths," *IEEE*

Fig. 7. Compare RDA and PDA with H.MCOP

- International Conference on Communications (ICC'98)*, June 1998.
- [18] A. Goel, K. G. Ramakrishnan, D. Kataria, and D. Logothetis, "Efficient Computation of Delay-Sensitive Routes for One Source to All Destinations," *IEEE INFOCOM'2001*, April 2001.
- [19] M. Garey and D. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*, New York: W.H. Freeman and Co., 1979.
- [20] H. C. Joksch, "The Shortest Route Problem with Constraints," *Journal of Mathematical Analysis and Applications*, vol. 14, pp. 191–197, 1966.
- [21] D. Lorenz and D. Raz, "A Simple Efficient Approximation Scheme for the Restricted Shortest Paths Problem," *Bell Labs Technical Memorandum*, 1999.
- [22] S. Sahni, "General Techniques for Combinatorial Approximation," *Operations Research*, vol. 26, no. 5, 1977.
- [23] Michalis Faloutsos, Petros Faloutsos, and Christos Faloutsos, "On Power-Law Relationships of the Internet Topology," *ACM Proceedings of SIGCOMM '99*, 1999.
- [24] B. M. Waxman, "Routing of Multipoint Connections," *IEEE Journal of Selected Area in Communications*, pp. 1617–1622, Dec. 1988.
- [25] H. De Neve and P. Van Mieghem, "A Multiple Quality of Service Routing Algorithm for PNNI," *IEEE ATM Workshop*, May 1998.

## APPENDIX A. PROOF OF THEOREM 1

Refer to Section III for the lines of the pseudo code of RDA (randomized discretization algorithm).

*Lemma 1:* It always holds that  $\delta[u, i] \geq 0, \forall u \in V, i \in [0..\lambda]$ .

*Proof:* It holds initially. The value of  $\delta$  changes only at Line 12. Suppose  $\delta[u, i] \geq 0$  and  $\delta[v, i'] \geq 0$  before `Relax_RDA(...)` is called. Because  $-\frac{r}{\lambda} \leq \Delta^r(u, v) \leq \frac{r}{\lambda}$ , Lines 6-7 make sure that  $error \geq 0$ . Hence,  $\delta[v, i'] \geq 0$  after Line 12. The lemma remains true after the call.  $\square$

*Lemma 2:* Let  $P_i^u$  be the path stored by  $\pi[u, i]$ . It always holds that  $d(P_i^u) \geq i\frac{r}{\lambda} + \delta[u, i], \forall u \in V, i \in [0..\lambda]$ .

*Proof:* Suppose it holds before `Relax_RDA(...)` is called.  $P_i^u \leq i\frac{r}{\lambda} + \delta[u, i]$ . The new path under consideration is  $P_i^u + (u, v)$ .

$$\begin{aligned} d(P_i^u + (u, v)) &= d(P_i^u) + d(u, v) \\ &\geq i\frac{r}{\lambda} + \delta[u, i] + d^r(u, v)\frac{r}{\lambda} + \Delta^r(u, v) \\ &= (i + d^r(u, v))\frac{r}{\lambda} + \delta[u, i] + \Delta^r(u, v) \end{aligned}$$

After Lines 4-8,  $d(P_i^u + (u, v)) \geq i'\frac{r}{\lambda} + error$ . After Line 12,  $\delta[v, i'] \leq error$ . Hence,  $d(P_i^u + (u, v)) = d(P_{i'}^v) \geq i'\frac{r}{\lambda} + \delta[v, i']$ . The lemma holds after the call.  $\square$

*Lemma 3:* Let  $P_i^u$  be the path stored by  $\pi[u, i]$ . It always holds that  $d(P_i^u) \leq (i + l(P_i^u))\frac{r}{\lambda}, \forall u \in V, i \in [0..\lambda]$ , where  $l(P_i^u)$  is the length (hops) of  $P_i^u$ .

*Proof:* Suppose it holds before `Relax_RDA(...)` is called.  $P_i^u \leq (i + l(P_i^u))\frac{r}{\lambda}$ . The new path under consideration is  $P_i^u +$

$(u, v)$ .

$$\begin{aligned} d(P_i^u + (u, v)) &= d(P_i^u) + d(u, v) \\ &\leq (i + l(P_i^u))\frac{r}{\lambda} + d^r(u, v)\frac{r}{\lambda} + \Delta^r(u, v) \\ &= (i + d^r(u, v))\frac{r}{\lambda} + \Delta^r(u, v) + l(P_i^u)\frac{r}{\lambda} \\ &\leq i'\frac{r}{\lambda} + (l(P_i^u) + 1)\frac{r}{\lambda} \end{aligned}$$

After Line 12,  $d(P_i^u + (u, v)) = d(P_{i'}^v) \leq (i' + l(P_{i'}^v))\frac{r}{\lambda}$ . The lemma holds after the call.  $\square$

*Theorem 1:* RDA solves the  $\varepsilon$ -approximation of DCLC in time  $O((m + n \log n)L/\varepsilon)$ .

*Proof:* We first prove that if RDA terminates, it solves the  $\varepsilon$ -approximation of DCLC. Consider an arbitrary node  $t$ . Let  $P_{s,t}$  be the cheapest feasible path. Assume this is the only path from  $s$  to  $t$ . Consider `Relax_RDA(...)` is called on a link  $(u, v)$  of  $P_{s,t}$ . After Lines 4-5,  $i' = i + d^r(u, v) = i + (d(u, v) - \Delta^r(u, v))\frac{\lambda}{r} = i + (d(u, v) - error + \delta[u, i])\frac{\lambda}{r}$ . After Lines 6-8, because  $error \geq 0$ ,  $i' \leq i + \delta[u, i]\frac{\lambda}{r} + d(u, v)\frac{\lambda}{r}$ . By Lemma 2,  $i + \delta[u, i]\frac{\lambda}{r} \leq d(P_i^u)\frac{\lambda}{r}$ . We have  $i' \leq (d(P_i^u) + d(u, v))\frac{\lambda}{r} \leq d(P_{s,t})\frac{\lambda}{r} \leq \lambda$ . Lines 9-12 will be executed. Eventually,  $P_{s,t}$  will be stored by  $\pi[t, i]$  for some  $i \leq \lambda$ .

Now if there exist other paths from  $s$  to  $t$  and one of them replaces  $P_{s,t}$  during the relaxation, the path must have a smaller cost than  $P_{s,t}$ . Hence, when RDA terminates, let  $p^t$  be the path returned by RDA for  $t$  with  $\min\{w[t, i] \mid i \in [0..\lambda]\}$ . We must have  $c(p^t) \leq c(P_{s,t})$ , and  $d(P^t) \leq (1 + \varepsilon)r$  because otherwise RDA won't terminate.

We now prove that RDA terminates in time  $O((m + n \log n)L/\varepsilon)$ . When  $\lambda \geq \frac{L}{\varepsilon}$ , by Lemma 3,  $\forall t \in V, d(P^t) \leq (\lambda + l(P^t))\frac{r}{\lambda} \leq r + l(P^t)\frac{r}{L} \leq (1 + \varepsilon)r$ . By Line 26, RDA terminates.

The time complexity of each execution of `RDA_Dijkstra(...)` is  $O((m + n \log n)\lambda)$ . Since  $\lambda$  doubles each time, the time of the last execution is larger than the combined time of all previous executions. Therefore, the complexity of RDA is  $O((m + n \log n)L/\varepsilon)$ .  $\square$

## APPENDIX B. PROOF OF THEOREM 2

Refer to Section IV for the lines of the pseudo code of RDA (randomized discretization algorithm).

*Lemma 4:* Let  $P_i^u$  be the path stored by  $\pi[u, i]$ . It always holds that  $z[u, i] \leq d(P_i^u), \forall u \in V, i \in [0..\lambda]$ .

The proof is trivial based on Line 8.

*Lemma 5:* Let  $P_i^u$  be the path stored by  $\pi[u, i]$ . It always holds that  $z[u, i] \geq i\frac{r}{\lambda}, \forall u \in V, i \in [0..\lambda]$ .

*Proof:* Suppose it holds before `Relax_PDA(...)` is called, namely,  $z[u, i] \geq i\frac{r}{\lambda}$  and  $z[v, i'] \geq i'\frac{r}{\lambda}$ . The new path under

consideration is  $P_i^u + (u, v)$ .

$$\begin{aligned} i' &= \lfloor \frac{z[u, i] + d(u, v)}{r} \lambda \rfloor \\ i' &\leq \frac{z[u, i] + d(u, v)}{r} \lambda \\ z[u, i] + d(u, v) &\geq i' \frac{r}{\lambda} \end{aligned}$$

After Line 8 is executed,  $z[v, i'] \geq i' \frac{r}{\lambda}$  remains true.  $\square$

*Lemma 6:* Let  $P_i^u$  be the path stored by  $\pi[u, i]$ . It always holds that  $d(P_i^u) \leq (i + l(P_i^u)) \frac{r}{\lambda}$ ,  $\forall u \in V, i \in [0..l]$ , where  $l(P_i^u)$  is the length (hops) of  $P_i^u$ .

*Proof:* Suppose it holds before `Relax_PDA(...)` is called.  $d(P_i^u) \leq (i + l(P_i^u)) \frac{r}{\lambda}$ . The new path under consideration is  $P_{i'}^u + (u, v)$ .

$$\begin{aligned} d(P_{i'}^u + (u, v)) &= d(P_{i'}^u) + d(u, v) \\ &\leq (i + l(P_{i'}^u)) \frac{r}{\lambda} + d(u, v) \\ &\leq z[u, i] + d(u, v) + l(P_{i'}^u) \frac{r}{\lambda} \\ &\leq i' \frac{r}{\lambda} + (l(P_{i'}^u) + 1) \frac{r}{\lambda} \end{aligned}$$

After Lines 5-8,  $d(P_{i'}^u + (u, v)) = d(P_{i'}^v) \leq (i' + l(P_{i'}^v)) \frac{r}{\lambda}$ . The lemma holds after the call.  $\square$

*Theorem 2:* PDA solves the  $\varepsilon$ -approximation of DCLC in time  $O((m + n \log n)L/\varepsilon)$ .

The proof is similar to that for Theorem 1 in Appendix A.

### APPENDIX C. PROOF OF THEOREM 3

*Theorem 3:* Given a path  $P$ , the mean of  $\Delta^r(P)$  is zero and the standard deviation of  $\Delta^r(P)$  is at most  $\frac{r\sqrt{l(P)}}{2\lambda}$ , regardless of the probability distributions of the link delays.

*Proof:* Consider an arbitrary link  $(u, v)$  on  $P$ .

$$\begin{aligned} \Delta^r(u, v) &= d(u, v) - d^r(u, v) \frac{r}{\lambda} \\ &= \begin{cases} d(u, v) - \lceil \frac{d(u, v)}{r} \lambda \rceil \frac{r}{\lambda} & \text{with prob. } p_1 = \frac{d(u, v)}{r} \lambda - \lfloor \frac{d(u, v)}{r} \lambda \rfloor \\ d(u, v) - \lfloor \frac{d(u, v)}{r} \lambda \rfloor \frac{r}{\lambda} & \text{with prob. } p_2 = 1 - p_1 \end{cases} \end{aligned}$$

The mean (or expected value) of  $\Delta^r(u, v)$  is

$$\begin{aligned} E(\Delta^r(u, v)) &= (d(u, v) - \lceil \frac{d(u, v)}{r} \lambda \rceil \frac{r}{\lambda}) \cdot p_1 \\ &\quad + (d(u, v) - \lfloor \frac{d(u, v)}{r} \lambda \rfloor \frac{r}{\lambda}) \cdot p_2 \end{aligned}$$

There are two cases.

- Case 1: If  $\frac{d(u, v)}{r} \lambda$  is an integer, i.e.,  $\frac{d(u, v)}{r} \lambda = \lceil \frac{d(u, v)}{r} \lambda \rceil = \lfloor \frac{d(u, v)}{r} \lambda \rfloor$ , then it is clear that  $E(\Delta^r(u, v)) = 0$ .

- Case 2: If  $\frac{d(u, v)}{r} \lambda$  is not an integer, then

$$\begin{aligned} p_2 &= 1 - \frac{d(u, v)}{r} \lambda + \lfloor \frac{d(u, v)}{r} \lambda \rfloor \\ &= \lceil \frac{d(u, v)}{r} \lambda \rceil - \frac{d(u, v)}{r} \lambda \end{aligned} \quad (12)$$

$$\begin{aligned} E(\Delta^r(u, v)) &= (d(u, v) - \lceil \frac{d(u, v)}{r} \lambda \rceil \frac{r}{\lambda}) \cdot (\frac{d(u, v)}{r} \lambda - \lfloor \frac{d(u, v)}{r} \lambda \rfloor) \\ &\quad + (d(u, v) - \lfloor \frac{d(u, v)}{r} \lambda \rfloor \frac{r}{\lambda}) \cdot (\lceil \frac{d(u, v)}{r} \lambda \rceil - \frac{d(u, v)}{r} \lambda) \\ &= 0 \end{aligned}$$

Denote  $E(\Delta^r(u, v))$  as  $\mu$  for clarity. Since the probability density function of  $d(u, v)$  is  $f_{u, v}(x)$ ,  $x \in [0, +\infty)$ , the variance of  $\Delta^r(u, v)$  is

$$\begin{aligned} V(\Delta^r(u, v)) &= \int_0^\infty [(x - \lceil \frac{x}{r} \lambda \rceil \frac{r}{\lambda} - \mu)^2 \cdot p_1 \\ &\quad + (x - \lfloor \frac{x}{r} \lambda \rfloor \frac{r}{\lambda} - \mu)^2 \cdot p_2] \cdot f_{u, v}(x) dx \\ &= \frac{r^2}{\lambda^2} \int_0^\infty [(\frac{x}{r} \lambda - \lceil \frac{x}{r} \lambda \rceil)^2 \cdot p_1 + (\frac{x}{r} \lambda - \lfloor \frac{x}{r} \lambda \rfloor)^2 \cdot p_2] \\ &\quad \cdot f_{u, v}(x) dx \end{aligned}$$

When  $d(u, v) = x$ ,  $p_1 = \frac{x}{r} \lambda - \lfloor \frac{x}{r} \lambda \rfloor$  by (7), and  $p_2 = \lceil \frac{x}{r} \lambda \rceil - \frac{x}{r} \lambda$  by (12). Hence,

$$\begin{aligned} V(\Delta^r(u, v)) &= \frac{r^2}{\lambda^2} \int_0^\infty [(\frac{x}{r} \lambda - \lceil \frac{x}{r} \lambda \rceil)^2 \cdot (\frac{x}{r} \lambda - \lfloor \frac{x}{r} \lambda \rfloor) \\ &\quad + (\frac{x}{r} \lambda - \lfloor \frac{x}{r} \lambda \rfloor)^2 \cdot (\lceil \frac{x}{r} \lambda \rceil - \frac{x}{r} \lambda)] \cdot f_{u, v}(x) dx \\ &= \frac{r^2}{\lambda^2} \int_0^\infty (\lceil \frac{x}{r} \lambda \rceil - \frac{x}{r} \lambda) \cdot (\frac{x}{r} \lambda - \lfloor \frac{x}{r} \lambda \rfloor) \cdot f_{u, v}(x) dx \\ &= \frac{r^2}{\lambda^2} \int_0^\infty (\lceil \frac{x}{r} \lambda \rceil - \frac{x}{r} \lambda) \cdot (1 - (\lceil \frac{x}{r} \lambda \rceil - \frac{x}{r} \lambda)) \\ &\quad \cdot f_{u, v}(x) dx \end{aligned}$$

Because  $y(1 - y)$ ,  $y \in [0, 1)$ , reaches its maximum value of  $1/4$  when  $y = 1/2$ , we have

$$\begin{aligned} V(\Delta^r(u, v)) &\leq \frac{r^2}{\lambda^2} \int_0^\infty \frac{1}{4} f_{u, v}(x) dx \\ &= \frac{r^2}{4\lambda^2} \end{aligned}$$

Therefore, given an arbitrary probability density function of  $d(u, v)$ , we showed that  $E(\Delta^r(u, v)) = 0$  and  $V(\Delta^r(u, v)) \leq \frac{r^2}{4\lambda^2}$ , for every  $(u, v)$  on  $P$ . The mean and the variance of  $\Delta^r(P)$  are

$$\begin{aligned} E(\Delta^r(P)) &= E(\sum_{(u, v) \text{ on } P} \Delta^r(u, v)) \\ &= \sum_{(u, v) \text{ on } P} E(\Delta^r(u, v)) = 0 \end{aligned}$$

$$\begin{aligned}
 V(\Delta^r(P)) &= V\left(\sum_{(u,v) \text{ on } P} \Delta^r(u,v)\right) \\
 &= \sum_{(u,v) \text{ on } P} V(\Delta^r(u,v)) \leq \frac{r^2 l(P)}{4\lambda^2}
 \end{aligned}$$

The standard deviation of  $\Delta^r(P)$  is

$$\sigma(\Delta^r(P)) = \sqrt{V(\Delta^r(P))} \leq \frac{r\sqrt{l(P)}}{2\lambda}$$

□



**Shigang Chen** received his B.S. degree in computer science from University of Science and Technology of China in 1993. He received M.S. and Ph.D. degrees in computer science from University of Illinois at Urbana-Champaign in 1996 and 1999, respectively. After graduation, he had worked with Cisco Systems for three years before joining University of Florida as an assistant professor in the Department of Computer & Information Science & Engineering. His research interests include network algorithms, quality of service, and sensor networks. He received IEEE

Communications Society Best Tutorial Paper Award in 1999. He was a guest editor for ACM/Baltzer Journal of Wireless Networks (WINET) and IEEE Transactions on Vehicle Technologies. He is serving as a TPC co-chair for the Computer and Network Security Symposium of IEEE IWCCC 2006. He served as a vice TPC chair for IEEE MASS 2005, a vice general chair for QShine 2005, a TPC co-chair for QShine 2004, and a TPC member for many conferences including IEEE ICNP, IEEE INFOCOM, IEEE SANS, IEEE ISCC, IEEE Globecom, etc. His email address is sgchen@cise.ufl.edu.



**Sartaj Sahni** is a Distinguished Professor and Chair of Computer and Information Sciences and Engineering at the University of Florida. He is also a member of the European Academy of Sciences, a Fellow of IEEE, ACM, AAAS, and Minnesota Supercomputer Institute, and a Distinguished Alumnus of the Indian Institute of Technology, Kanpur. In 1997, he was awarded the IEEE Computer Society Taylor L. Booth Education Award “for contributions to Computer Science and Engineering education in the areas of data structures, algorithms, and parallel algorithms”, and in 2003, he was awarded the IEEE Computer Society W. Wallace McDowell Award “for contributions to the theory of NP-hard and NP-complete problems”. Dr. Sahni was awarded the 2003 ACM Karl Karlstrom Outstanding Educator Award for “outstanding contributions to computing education through inspired teaching, development of courses and curricula for distance education, contributions to professional societies, and authoring significant textbooks in several areas including discrete mathematics, data structures, algorithms, and parallel and distributed computing.” Dr. Sahni received his B.Tech. (Electrical Engineering) degree from the Indian Institute of Technology, Kanpur, and the M.S. and Ph.D. degrees in Computer Science from Cornell University. Dr. Sahni has published over three hundred research papers and written 15 texts. His research publications are on the design and analysis of efficient algorithms, parallel computing, interconnection networks, design automation, and medical algorithms.

Dr. Sahni is a co-editor-in-chief of the Journal of Parallel and Distributed Computing, a managing editor of the International Journal of Foundations of Computer Science, and a member of the editorial boards of Computer Systems: Science and Engineering, International Journal of High Performance Computing and Networking, International Journal of Distributed Sensor Networks and Parallel Processing Letters. He has served as program committee chair, general chair, and been a keynote speaker at many conferences. Dr. Sahni has served on several NSF and NIH panels and he has been involved as an external evaluator of several Computer Science and Engineering departments.



**Meongchul Song** received the BEng and MEng degrees in computer engineering from Kyungpook National University, Republic of Korea in 1991 and 1993, respectively and the Ph.D. degree in computer science from University of Florida in 2005. Prior to joining University of Florida, he was a software engineer in the Agency for Defense Development, Republic of Korea from 1993 to 1999. He is currently a senior engineer in the Systems R&D Laboratories, Samsung Electronics Co., Ltd. His research interests include networks and approximation algorithms. He

is a member of the IEEE.